

Specifications:

Model No.	PFH-9210-60	PFH-9210-620	PFH-9210-660
Reading Range	Max. 50 ~ 60cm	Max. 6 meters	Max. 40 cm for EM card Max.6 meters for Hand free card
Buzzer	Yes (Built - in)	No (Built-in driver for external buzzer)	
Applicable Card	EM-125KHz PG-PROXS-L-Y1	PFH-620	Standard EM card & PFH-660
Operating Frequency	125 KHz	433.9 MHz & 125KHz	125 KHz & 433.9 MHz
Modulation	Transmit coded - ASK, Receiving - Super Heterodyne		
Output Format	RS-485, RS-232C, Wiegand or Pegasus format ABA Track II magstripe format		
Indications	2 color (Red and Amber)	3 color LED (Red , Amber and Green)	4 color LED (Red, Green, Amber and Light)
Mounting / Waterproof	Surface mount		
Operating Temp.	-10°C ~ 55°C		
Humidity	20% ~ 90%RH (Non condensing)		
Dimension (W)x(L)x(H) mm	270 (W) x 270 (L) x 39 (H)		
(W)x(L)x(H) inch	10.63 (W) x 10.63 (L) x 1.54 (H)		
Operating Voltage / Current	12 VDC/200mA	15 VDC/300 mA	12V DC / 300 mA
Material	ABS		
Weight	2.00 Kg ± 5%		
Color	Black		

Applicable Card and Tag

Model No.	PG-PROXS-L-Y1	PFH-300	PFH-320	PFH-620	PFH-660
Dimension	54 x 85 x 1.8	54 x 85 x 8	54 x 85 x 8	54 x 85 x 8	54 x 85 x 8
(W)x(L)x(T) mm	2.13x 3.35 x 0.07	2.13x 3.35 x 0.31	2.13x 3.35 x 0.31	2.13x 3.35 x 0.31	2.13x3.35 x 0.31
(W)x(L)x(T) inch					
Material	PVC	ABS			
Working Frequency	125 KHz	433.9 MHz	433.9 MHz		Dual Functions 1.Hand free card 433.9MHz for car 2.Proximity card 125KHz for personal
Battery	No battery	Built-in 3V lithium battery (active)			
Operating Temp.	-10°C ~ 70°C				
Humidity	0% ~ 90%RH (Non condensing)				
Color	White	Brown	Light Gray		
Weight	38 g				