



ESD tester



PE168-STG-2

Product Description

- This ESD tester is designed with 3.5 inch color LCD TFT Touch screen to display digital resistance value with different color (green, red & yellow) for simply identification.
- Complies with standards GJB 3007-97, SJ/T 10694-2006 and ANSI ESD S20.20
- Supports to check personnel grounding of either wrist straps or footwear.
- The standard resistance and near failure resistance can be set from the color screen login.
- Supports stand-alone or on-line mode of judgment.



Main application field

SMT production line, clean room such as semiconductor fab, high tech RD room, or military ESD sensitive areas, explosive processing areas, maintain or calibration areas for aero space industries, pharmacy , bio-chemical and hospital ESD restraint areas.



Specification

Power supply	: DC 8~12V 100mA
Weight	: 622 g±5%
Dimension	: 162x102x27.5mm
Output signal	: ThreePASS Channels
Test voltage	: 10V±10%
Resistance range	: 100KΩ~1000MΩ
Accuracy	: ±10%
Test period	: ≤0.35 S/Channel
Communication	: RS-485
Operating temperature	: Indoor, 0°C~50°C
Operating humidity	: 0%~80%
Voice Alarm	: Yes
Resistance value display	: Yes
Display screen	: 3.5 inch color LCD TFT Touch screen display, split screen display
Measuring types	: Wrist wrap of single line or double lines and ESD shoes
Wrist sockets	: One wire with two sockets, two wires with two sockets.
Test button	: Touching button, unlike press button with spring, durable and stable.
Pass/NG Output	: PASS/NG signal : Relay output in dry contact signal

PONGEE INDUSTRIES CO., LTD.

5F., No.738, Chung-Cheng Rd., Chung-Ho District, New Taipei City 23511, Taiwan

Tel : 886-2-82280198

Fax : 886-2-82280191

E-mail : pongee@pongee.com.tw

Website: <http://www.pongee.com>

We reserve the right to change the specification without prior notice or obligation!



FM 39868



20200817