


Micro Power 125KHz FSK H.I.D. Module

PXHD-12W-LW1

Micro Power
10~15 μ A only



PXHD-12W-LW
(Optional)


Introduction

PXHD-12W-LW1 is ultra-low power modules designed to operate from 4volt to 9volt. At its lower power setting is consumes just 15 μ A making these modules the perfect low power alternative to conventional readers. The modules support Wiegand 25~40 data formats and able to read H.I.D. or compatible cards and ideal for fixed and portable applications. OEM/ODM orders are welcome.

Specifications

RFID frequency	: 125KHz FSK
Applicable cards	: H.I.D. or compatible card
Reading range	: DC 4V: 30 mm / DC 9V: 35 mm
Output format	: Wiegand 25~40 bits
Power input	: DC 4V~DC 9V
Standby current	: 10~15 μA
Working current	: 21.3~23.8 mA
Dimensions(L) ×(W)	: 43.2 x 33 mm / 1.7 x 1.3 inch
Operating temperature	: -30°C~65°C
Storage temperature	: -40°C~85°C

Dimension: (Unit: mm / inch)



Optional Antenna

Antenna Model No.	Dimension	Reading Range (Depending on tag size, tag type)
R-17-54TS/450UH	Internal diameter: 70 x 54 mm Outside diameter: 74 x 59 mm Height: 5 mm	Card (T:1.8mm): 35 mm
		Card (T:0.8mm): 30 mm
R-17-PP110/COIL	Internal diameter: 84 x 35 mm Outside diameter: 86 x 38 mm Height: 3 mm	Card (T:1.8mm): 35 mm
		Card (T:0.8mm): 30 mm
R-17-PEI101/COIL	Internal diameter: 34 x 34 mm Outside diameter: 23 x 23 mm Height: 2 mm	Card (T:1.8mm): 28 mm
		Card (T:0.8mm): 24 mm

PONGEE INDUSTRIES CO., LTD.

5F., No.738, Chung-Cheng Rd., Chung-Ho District, New Taipei City 23511, Taiwan

Tel : 886-2-82280198

Fax : 886-2-82280191

E-mail : pongee@pongee.com.tw

Website: <http://www.pongee.com>

We reserve the right to change the specification without prior notice or obligation!



20190830