












Pongee Industries Co., Ltd.

HF RFID Read Module - Mifare & FeliCa Series

20240131

Compatibility	Dimension(mm)	 Model No. (best-seller)	Features	Datasheet
Mifare, Mifare Ultralight, FeliCa	53x23 	PXFC-01SN/T	•Without internal antenna (Requires external 13.5MHz antenna) •Support UART(TTL) •Reading Range: Depending on antenna size •Power Voltage: DCSV	Download
Mifare, Mifare Ultralight, FeliCa	29x23 	PXFC-13SN/R2	•Without internal antenna (Requires external 13.5MHz antenna) •Support RS-232 •Reading Range: Depending on antenna size •Power Voltage: DCSV	Download
		PXFC-13SN/W26	•Without internal antenna (Requires external 13.5MHz antenna) •Support Wiegand 26bits •Reading Range: Depending on antenna size •Power Voltage: DCSV	Download
		PXFC-13SNW34	•Without internal antenna (Requires external 13.5MHz antenna) •Support Wiegand 34bits •Reading Range: Depending on antenna size •Power Voltage: DCSV	Download
Mifare, Mifare Ultralight, FeliCa	58x29 	PIFC-18EU1D04	•With internal antenna •Support USB (Decimal, 10 digits, 4byte) •With LED indicator •Reading Range: Max. 4cm •Power Voltage: By USB	Download
Mifare, Mifare Ultralight, FeliCa		PIFC-18SN/W26T	•With internal antenna •Support Wiegand 26bits/UART(TTL) •Reading Range: Max. 3cm •Power Voltage: DCSV	Download
		PIFC-18SNW34T	•With internal antenna •Support Wiegand 34bits/UART(TTL) •Reading Range: Max. 3cm •Power Voltage: DCSV	Download
Mifare, Mifare Ultralight, FeliCa		PIFC-18SN/U1W26T	•With internal antenna •Support USB/Wiegand 26bits/UART(TTL) •Reading Range: Max. 3cm •Power Voltage: DCSV	Download
		 PIFC-18SN/U1W34T	•With internal antenna •Support USB/Wiegand 34bits/UART(TTL) •Reading Range: Max. 3cm •Power Voltage: DCSV	Download
		PIFC-18SNU1W34TS	•With internal antenna •Support USB/Wiegand 34bits/UART(TTL) •Reading Range: Max. 3cm •Power Voltage: DCSV •Card no. in positive	Download
		PIFC-18U1W66T	•With internal antenna •Support USB, Hexadecimal code according to card no. •Support Wiegand 66 bits(FeliCa), Wiegand 34 bits(Mifare) /UART(TTL) •Reading Range: Max. 4cm •Power Voltage: By USB	Download
		 PIFC-18U1W66TS	•With internal antenna •Support USB, Hexadecimal code according to card no. •Support Wiegand 66 bits(FeliCa), Wiegand 34 bits(Mifare) /UART(TTL) •Reading Range: Max. 4cm •Power Voltage: By USB •Card no. in positive	Download
Mifare, Mifare Ultralight, FeliCa	32x32x8 	PIFC-HSN/W26T	•With internal antenna •Support Wiegand 26bits/UART(TTL) •Reading Range: Max. 3cm •Power Voltage: DCSV	Download
		PIFC-HSN/W34T	•With internal antenna •Support Wiegand 34bits/UART(TTL) •Reading Range: Max. 3cm •Power Voltage: DCSV	Download