

陽極鎖系列

鵬驥實業有限公司 20221201



型 號		DA-64	DA-64NS	DA-64A/D DA-64ADV	DA-64RA/D	DA-64A/D/B-I	DA-62B	DA-66S	DA-66SL	DA-70
特 點		斷電開	送電開	斷電開	斷電開	斷電開	斷電開	斷電開	送電開	斷電開
工 作 電 壓		DC 12V	DC 12V	DC11V~16V DC12V~24V	DC11V~16V	DC11V~16V	DC12V	DC12V	DC12V	DC12V
待 機 電 流		18mA	18mA	110~90mA 100~50mA	100mA	90mA	310mA	120mA	230mA	250mA
啟 動 電 流		440mA	600mA	1000~900mA 800~500mA	850mA	780mA	1040mA	1000mA	1000mA	900mA
開 門 延 遲 時 間 (秒)		3, 6, 10	3, 6, 10	3, 7, 8	3, 6, 10	立即下鎖	3, 6, 10	4, 5, 10	4, 5, 10	1, 2, 3, 4, 5
電 源 指 示 燈		●	●	●	●	●	---	●	●	---
狀 態 指 示 燈		●	●	---	●	---	---	---	●	---
門 位 值 測		●	●	●	●	●	●	●	●	●
尺 寸 (L x W x D) 公 厘	面 板	204 x 33 x 3					222 x 33 x 3	203 x 25.4 x 3	243 x 25.4 x 3	203 x 33 x 3
	鎖 體	132 x 30 x 42					189 x 32 x 40	140 x 23 x 33	187 x 23 x 33	143 x 32 x 40
認 證		CE					---	CE	CE	---
專 利		●	●	---	---	---	---	---	---	---
客 製 功 能		---	---	客製功能 選購明細	---	客製功能 選購明細	---	客製功能 選購明細	---	---
選 購 配 件	DAR-24 緊急陽極鎖 開鎖器 專利認證!			---	●	---	---	---	---	內附支架組
	PG-B64 外掛盒			●	---	●	●	●	---	
	PG-DASTC-2 玻璃夾具 (可夾玻璃最 厚 12MM)			●	---	●	●	●	---	
	SL-70E 歐規單邊鎖心			---	---	---	---	---	●	

DA-64A/D 系列選購表



DA-66 系列選購表

產品		功 能				
		工作電壓	開門延遲時間	延遲下鎖時間	立即下鎖	電源指示燈
	DA-66S	DC 12V	4,5,10	3,4		●
		斷電開陽極鎖，DC12V，具開門延遲時間/關門至定點後延遲下鎖時間/具電源指示燈				
	DA-66S-I-VM	DC 12V			●	●
		斷電開陽極鎖，DC12V，立即下鎖，具電源指示燈				



產 品